



RELOADING DATA FOR COPPER PLATED BULLETS

BULLET				GUN POWDER			VELOCITY	BARREL	POWER FACTOR
Weight (grs)	Type	Mfg.	OAL (mm)	Mfg.	Type	Weight (grs)	Vo(fps)	(mm)	
123	9mm RN	LOS	29	Vihtavuori	N320	3,9	1078	127	133
123	9mm FP	LOS	28,8	Vihtavuori	N320	3,9	1052	127	129
123	9mm HP	LOS	28,8	Vihtavuori	N320	3,9	1050	127	129
123	9mm RN	LOS	29	Vihtavuori	N340	4,7	1104	127	136
123	9mm FP	LOS	28,8	Vihtavuori	N340	4,7	1068	127	131
123	9mm HP	LOS	28,8	Vihtavuori	N340	4,7	1064	127	131
145	9mm RN	LOS	29	Vihtavuori	N340	3,8	915	127	133
145	9mm FP	LOS	28,8	Vihtavuori	N340	3,8	916	127	133
145	9mm HP	LOS	28,8	Vihtavuori	N340	3,8	923	127	134
148	38/357 WCHB	LOS	31	Vihtavuori	N320	3,3	701	102	104
158	38/357 RNFP	LOS	40,2	Vihtavuori	N340	7,4	1198	102	189
158	38/357 HP	LOS	40,2	Vihtavuori	N340	7,4	1202	102	190
180	40RN	LOS	29	Vihtavuori	N340	5,5	967	127	174
180	40RNFP	LOS	28,7	Vihtavuori	N340	5,5	950	127	171
230	45RN	LOS	32	Vihtavuori	N320	4,9	770	127	177
230	45RN	LOS	32	Vihtavuori	N340	5,9	801	127	184

WARNING

Follow the Reloading Safety Instructions before starting the reloading process.

Since LOS company has no possibility to control either the handling or storage of the reloading components or the reloading process itself, LOS company can not accept any liability for the possible direct or indirect effects of the use of LOS company components.